


Multi-Protocol Data Distribution Server



FEATURES

- Drop in Replacement for MPS1000
- Supports the MPS API
- Supports the Sunhillo Core Software including Tier 1, 2
- Up to 16 High-Speed WAN-Ports
- Two Gigabit Ethernet Ports
- Optional COM Express Single Board Computer
- SNMP Support

The **Ventnor** is the next generation product from Sunhillo. Offering a drop in solution for existing MPS1000 customers, the Ventnor provides enhanced capabilities over the existing MPS1000 product, while addressing multiple markets with Sunhillo's feature rich software.

The Ventnor provides access to the MPS application programming interface (API) and the associated integrated protocol suite. These protocols enable development engineers to proceed directly to integration and application development efforts.

Additionally, the Ventnor is the first product that completely integrates the MPS API with the

Sunhillo surveillance sensor data formatting, filtering, and protocol conversion capabilities. Support for an optional COM Express Single Board Computer is also available within the Ventnor, providing additional customer specific functionality and processing capabilities.

The Ventnor offers the following network interface and conversion capabilities:

- **Serial-to-LAN** – receives radar data through up to 16 serial ports and multicasts/unicasts the data onto a Local Area Network (LAN)
- **LAN-to-Serial** – receives data via the LAN and transmits data out onto serial port connection(s).

- **Serial-to-Serial** – receives up to 16 lines of serial data and multiplexes the data for transmission on a single serial line.

- **LAN-to-LAN** – receives data via the LAN and multicasts/unicasts it onto the LAN.

Sunhillo's comprehensive suite of protocols provides complete connectivity solutions for Radar, TADIL-B, HDLC, Async, and SBSI protocols.

Part Number:
070-08-VNT-S01
070-08-VNT-S02
070-08-VNT-S03
070-08-VNT-S04

Description:
Ventnor, 8-Port, Single Power Supply
Ventnor, 8-Port, Dual Power Supply
Ventnor, Tier 1, 8-Port, Single Power Supply
Ventnor, Tier 1, 8-Port, Dual Power Supply

070-16-VNT-S01
070-16-VNT-S02
070-16-VNT-S03
070-16-VNT-S04

Ventnor, 16-Port, Single Power Supply
Ventnor, 16-Port, Dual Power Supply
Ventnor, Tier 1, 16-Port, Single Power Supply
Ventnor, Tier 1, 16-Port, Dual Power Supply

Part Number:
070-U-PS150
PT-ACC334-11919
PT-ACC334-12274
PT-ACC334-11969
PT-ACC334-12273
PT-ACC334-11921
070-U-CONS
090-CBL-HDMI01

Description:
Ventnor, 150W Power Supply Module
4 x RS232 Hydra Cable, DTE with jackscrews
4 x RS232 Hydra Cable, DTE with thumbscrews
4 x EIA530 Hydra Cable, DTE with jackscrews
4 x EIA530 Hydra Cable, DTE with thumbscrews
4 x RS449 Hydra Cable (Pin), DTE with jackscrews
Ventnor, Console Cable Kit
6.6' HDMI to Micro HDMI Cable

Part Number:
070-08-VCOM-S01
070-08-VCOM-S02
070-08-VCOM-S03
070-08-VCOM-S04

Description (with COM Express):
Ventnor, 8-Port, Single Power Supply
Ventnor, 8-Port, Dual Power Supply
Ventnor, Tier 1, 8-Port, Single Power Supply
Ventnor, Tier 1, 8-Port, Dual Power Supply

070-16-VCOM-S01
070-16-VCOM-S02
070-16-VCOM-S03
070-16-VCOM-S04

Ventnor, 16-Port, Single Power Supply
Ventnor, 16-Port, Dual Power Supply
Ventnor, Tier 1, 16-Port, Single Power Supply
Ventnor, Tier 1, 16-Port, Dual Power Supply

Technical Specifications

Serial Port Controls

RS-232 (V.28), RS-422, X.21 (V.11), V35 (V.35 & V.28),
EIA-530A (V.10 & V.11), RS-449/V.36 (V.10 & V.11), RS-485

Serial Port Controls (available as 8 or 16 ports)

RS-232 (V.28), X.21 (V.11), EIA-530 (V.10 & V.11), EIA-530A
(V.10 & V.11), RS-449/V.36

Ethernet

10BASE-T, 100BASE-T, 1000BASE-T, IEEE-802.3

Protocols

Synchronous, Asynchronous, HDLC/SDLC Suite, Radar
Suite, Bi-Sync, Mono-Sync, TCP/IP, UDP/IP

Message Formats

ASTERIX (e.g., CAT 01, 02, 33, 34, 48, and others),
CD-2, ASR-9/11, Mode 4, Mode S, MAR, TPS75, ARTS,
AIRCAT-500, ECGP, SGF, ADS-B, custom, and more

Clock Sources

DCE, DTE, Partial Split Clock, drive TXC, receive RXC

Power

- Power usage: 12W Max per unit - Standard Configuration
60W Max per unit - COM Express
- 100-240 VAC, 50-60Hz, 2-4A
- 1U Modular AC Power Supply
- Hot-swappable redundant configuration available

Additional Ports

- Mini USB for console
- Two USB ports (Optional COM Express)
- HDMI (Optional COM Express)

Dimensions

- Height: 1.61in / 41mm (Standard 1U)
- Width: 19in / 482mm
- Depth: 11.25in / 285.75mm

Environmental

- Storage Temperature: -50°C to +60°C
- Operating Temperature: 0°C to +50°C
- Relative Humidity Range: 10 – 90%, noncondensing
- Operating Altitude: -300' to 10,000' per MIL-STD-810G

Certifications and Compliance

- CE Marking
- FCC Part 15, Class B
- RoHS2 Directive 2011/65/EU
- ETL for Canada and US, 3023031
- UL/CSA/IEC/EN 60950-1
- UL/CSA/IEC/EN 62368-1

MTBF

- 16 Port, Single Power Supply
 - 313,023 hours
 - 16 Port, Single Power Supply, COM Express
 - 225,125 hours
- *Additional MTBF data is available by request



Sunhillo Corporation
444 Kelley Drive, West Berlin, NJ 08091-9210 USA

+1 856.767.7676

+1 856.767.9557

sales@sunhillo.com

For more information visit us at www.sunhillo.com